

RAVELLI SRL
Via Kupfer, 31
25036 Palazzolo sull'Oglio (BS)
Tel. +39 030 7402939 Fax +39 030 7301758
info@ravelligroup.it - www.ravelligroup.it

## **DECLARATION OF PERFORMANCE**

Declaration of performance according to Regulation (EU) 305/2011

## n. 057CPR13.07

- Unique identification code of the product type: 010-00-001A, residential space heating appliance fired by wood pellets EN 14785:2006
- Type, batch or serial number or any other element allowing identification of the construction product as required under Art. 11 (4): ARIA
- Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: Residential space heating appliance fired by wood pellets
- Name, registered trade name or registered trade mark and contact address of the manufacturer as required by Art. 11 (5); Ravelli s.r.l.

Via A. Kupfer, 31

25036 Palazzolo s/O (Bs) Italia

- 5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12 (2):
- System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: System 3
- In case of the declaration of performance concerning a construction product covered by a harmonised standard:
   The notified laboratory TÜV Rheinland Energie und Umwelt GmbH (NB 2456) performed the determination of the product type on the basis of type testing under system 3 and issued test report K14332014T1

8. Declared performance

| Harmonized technical specification:                | EN 14785:2006   |  |  |
|--|---|--|--|
| Essential characteristics                          | Performance   |  |  |
| Fire safety  |   |  |  |
| Reaction to fire                                   | A1  |  |  |
| Distance to combustible materials                  | Minimum distances (mm): rear = 100 sides = 200 front = 800 ceiling = 400 floor =  |  |  |
| Risk of burning fuel falling out                   | Pass  |  |  |
| Emission of combustion products (at 13% of $O_2$ ) | Nominal heat output CO 0.007 % NOx 130.8 mg/Nm³ OGC 6.2 mg/Nm³ PM 15.0 mg/Nm³ Reduced heat output CO 0.031 % OGC 8.0 mg/Nm³ |  |  |
| Surface temperature                                | Pass  |  |  |
| Electrical safety                                  | Pass  |  |  |
| Cleanability                                       | Pass  |  |  |
| Maximum operating pressure                         | 000   |  |  |
| Flue gas temperature at nominal heat output        | 157.2 °C  |  |  |
| Mechanical resistance(to carry a chimney/flue)     | NPD   |  |  |
| Nominal heat output                                | 5.3 kW  |  |  |
| Room heating output                                | 5.3 kW  |  |  |
| Water heating output                               |   |  |  |
| Епсіенсу   | П 89.4 % Nominal heat output<br>П 90.8 % Reduced heat output  |  |  |

| 9, | The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance |
|----|--|
|    | is issued under the sole responsibility of the manufacturer identified in point 4.   |

| Signed for and | on behalf of the manufacturer |      | Stefano Ravelli, CEO | / (dame and stile) |
|----------------|-------------------------------|------|----------------------|--------------------|
| Place          | Palazzolo s/O                 | Date | 6-11-2014            | Sign_              |