Ravelli Via Kupfer, 31 il fuoco intelligente

RAVELLI S.p.A. 25036 Palazzolo sull'Oglio (BS) Tel. + 39 030 7402939 Fax +39 030 7301758 info@ravelligroup.it - www.ravelligroup.it

## **DECLARATION OF PERFORMANCE** Declaration of performance according to Regulation (EU) 305/2011

## n. 086CPR13.07

1. Unique identification code of the product type:

012-00-002A, residential space heating appliance fired by wood pellets EN 14785:2006

- Type, batch or serial number or any other element allowing identification of the construction product as required under Art. 11(4): 2. DUAL 7 GLASS
- Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: 3. Residential space heating appliance fired by wood pellets
- 4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required by Art. 11 (5):
- Ravelli S.p.A. Via A. Kupfer, 31
- 25036 Palazzolo s/O (Bs) Italia
- Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2); 5
- 6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V System 3
- 7.
- In case of the declaration of performance concerning a construction product covered by a harmonised standard; The notified laboratory TÜV RheinlandEnergie GmbH (NB 2456) performed the determination of the product type on the basis of type testing under system 3 and issued test report K18492016T1
- 8 Declared performance

Harmonizedtechnicalspecification:	EN 14785:2006
Essentialcharacteristics	Performance
Firesafety	• • • • • • • • • • • • • • • • • • • •
Reaction to fire	A1
Distance to combustiblematerials	Minimum distances (mm): rear = 100 sides = 200 front = 800 ceiling = floor =
Risk of burning fuel falling out	Pass
Emission of combustion products (at 13% of O2)	Nominal heat output CO 0.003 % NOx 131.3 mg/Nm <sup>3</sup> OGC 2.3 mg/Nm <sup>3</sup> PM 13.05 mg/Nm <sup>3</sup> Reduced heat output CO 0.021 % OGC 4.1 mg/Nm <sup>3</sup>
Surface temperature	Pass
Electricalsafety	Pass
Cleanability	Pass
Maximum operating pressure	-
Flue gas temperature at nominal heat output	154.05 °C
Mechanical resistance(to carry a chimney/flue)	NPD
Nominal heat output	6.6 kW
Room heating output	6.6 kW
Water heating output	•
Efficiency	П91.75 % Nominal heat output П92.51 % Reduced heat output

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for	and on behalf of the man	ufacturerGio	vanni Scarlini, CEO	0	(nature and title)	_
Place	Palazzolo s/O	Date	<b>I-9-2016</b>	_ Sign_	Hel	V
					2	